



SHRI VISHWAKARMA SKILL UNIVERSITY

(State University enacted under the Government of Haryana Act 25, 2016)

UAC Form – 12/12

[Referred to in Rule 12.1 (ii).55]

SVSU/ITCELL/2026/NIQ/ 03

Dated: 24 /03 /2026

Notice Inviting Quotations

Subject: Notice Inviting Quotation for CCTV installation HVC residence.

Scaled quotations are invited from the manufacturers/exclusive distributors/ authorized dealers/suppliers/re-sellers for the items detailed below:

Sr. No.	Description of Items	Quantity
1	16 Ch. H.265 Network Video Recorder Support 16 Channel IP Camera Input H.265/H.264 dual codec decoding Up to 8MP resolution preview and playback, Max 160Mbps incoming bandwidth Support 1 or 2 SATA HDDs up to 20 TB, 2 USB ports (2.0) HDMI/VGA simultaneous video output Support Multi-brand network cameras ONVIF Version 2.4 conformance Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro Processor	1
2	Indoor Camera 1/2.9" 4MP PS CMOS Image Sensor (0.8758 Centimeters) Max. 4MP (2688 × 1520)/ (2560x1440)@25/30 fps Instastream, H.265, H.264, H.264H, H.264B, MJPEG Support Triple stream, WDR (120dB), Day/Night (ICR), 3D NR, ROI, AWB, AGC, BLC, HLC, Digital 3.6mm fixed Lens IR Range of 30 Mtr., Warm Light Range of 30 Mtr., PoE, IP67 Support Built-in Mic	3
3	Image Sensor: '1/2.7" 8MP Progressive Scan CMOS Effective Pixels: 3840 × 2160 Maximum Resolution: 8MP (4K UHD) Frame Rate: 8MP @ 20 fps, 4MP @ 25/30 fps Lens Type: Motorized Varifocal Focal Length: 2.7 mm – 13.5 mm Max Aperture: F1.4 Video Compression: Interstream, H.265, H.264, H.264H / H.264B, MJPEG (sub-stream) Wide Dynamic Range: 120 dB WDR Noise Reduction: 2D NR / 3D NR, Backlight Compensation: BLC / HLC. White Balance: Auto / Manual / Outdoor / Street lamp, Day/Night Mode: Auto (ICR) / Color / B&W, IR Distance: Up to 60 meters Warm Light Distance: 60 meters, IR LEDs: Multi-core dual light (IR +warm light), Smart IR: Supported	10
4	Storage – 16 TB	As mentioned
5	POE Switch, 16 port 10/100/1000 Mbps gigabit ethernet ports, 2 SFP port, 150watts available PoE, Flow control for protection against data loss, Maximum distance of 250m, Light protection 6KV, Operating Temperature: 0 to 40 deg C (32 to 104 deg F)	1



6	CAT6 UTP Cable (305 mtr) supports Gigabit Ethernet (1000 Base-T) standard. Operates at a bandwidth up to 250 Mhz.	5
7	HDMI 5 meter, Maximum Resolution: Full HD 1080p Supported Formats: 480p, 720p, 1080i, 1080p, 3D Support: Yes, HDMI Version: Typically, HDMI 1.4 Data Transfer Rate: Up to 18 Gbps HDMI with Ethernet: Supported LED / Smart TV, NVR / DVR, Laptop / Desktop, Projector, Set-top box	
8	PVC BOX for camera	
9	6U Rack	13
10	Online UPS 1 KVA, Capacity: 1 KVA / 800 W, UPS Type: Online Double Conversion Phase: Single Phase Input / Single Phase Output DC System Voltage: 24 VDC Input Voltage Range: 110 VAC \pm 5% – 300 VAC \pm 5% Frequency Range: 40 Hz – 70 Hz Power Factor: \geq 0.99 at full load Phase: Single phase with ground Rated Output Voltage: 200 / 208 / 220 / 230 / 240 VAC Voltage Regulation: \pm 1% (battery mode) Output Waveform: Pure Sine Wave Frequency (Battery Mode): 50 Hz \pm 0.25 Hz or 60 Hz \pm 0.3 Hz Current Crest Ratio: 3:1 Battery Type: SMF (Sealed Maintenance Free) Battery Quantity: 2 \times 12V / 9Ah (In-Built Batteries) Battery Voltage: 24V system Charging Current: 1A Over Voltage Cut-off Device (OVCD), Static Bypass for reliability Short Circuit, Protection Surge Protection, Smart LCD Display	1
11	LED 43 inch Display Screen Size: 1.08 m (43 inch) Display Type: LED Resolution: 4K UHD (3840 \times 2160), Picture Engine: Crystal Processor, 4K HDR: HDR / HDR10+ supported, Sound Output: 20 W RMS Speaker Type: 2 Channel Object Tracking Sound: OTS Lite, Adaptive Sound: Yes, HDMI Ports: 3 USB Ports: 1 \times USB-A Wi-Fi: Yes (built-in), Bluetooth: Yes RF Input: 1 IP, Control: Yes Power Supply: AC 220–240 V, 50/60 Hz Maximum Power Consumption: ~110 W	1
12	Conduct Pipe 25 Mm for Cat-6 Wire (Bundle/packet)	4
13	Conduct Pipe Band for Cat-6 Wire (bundle/packet)	2
14	Installation and commissioning of complete setup with any accessories required for installation	----

For any Query contact on itcell@svsu.ac.in.

The following charges and terms may be spelt out in your offer clearly:

- i. Rates quoted shall be **inclusive of all taxes, packing, forwarding, and delivery** at SVSU, Dudhola, Palwal, and Haryana–121102 within 05 Days.
- ii. **GST, if applicable, shall be clearly mentioned separately** in the quotation.
- iii. **Payment Terms:** As per SVSU norms.
- iv. **Delivery/Execution Period:** To be specified by the bidder.
- v. **Guarantee/Warranty Period:** To be specified by the bidder, wherever applicable.
- vi. **After-Sales Service:** As applicable.
- vii. **Installation Charges, if any:** To be quoted separately.
- viii. **Validity Period of the Quotation:** Minimum 180 days from the date of opening of NIQ.
- ix. **Bank Draft charges, if any:** To be borne by the bidder.

- x. **Miscellaneous charges** such as Packing & Forwarding, Insurance, etc., if any, shall be clearly indicated.
- xi. SVSU reserves the right to accept or reject any or all NIQs, wholly or partly, and to cancel the NIQ at any stage without assigning any reason.
- xii. The sealed quotations, super-scribed with the subject **“Quotation for CCTV installation HVC residence”**, complete in all respects, must reach the office of the undersigned latest by 06 / 04 / 2026 at 17:00 hrs at the following address:

In-Charge (ITCELL)
ITCELL Branch, 2nd Floor, Vallabhi Bhawan
Shri Vishwakarma Skill University
Village Dudhola, Palwal, Haryana-121102

The quotations must be submitted in original on firm letterhead with stamp through Registered Post/Speed Post/Courier or by hand, as the procurement process is to be carried out on the basis of hard copy submissions.



In-Charge
IT-Cell, SVSU

Annexure-I Proforma for Financial Bids

(To be put in separately under Sealed Cover)

01. Name of the Company:-----

02. Address:- -----

03. Contract No. & E-mail ID.-----

Sr. No.	Description of Items	Quantity	Rates
1	16 Ch. H.265 Network Video Recorder Support 16 Channel IP Camera Input H.265/H.264 dual codec decoding Up to 8MP resolution preview and playback, Max 160Mbps incoming bandwidth Support 1 or 2 SATA HDDs up to 20 TB, 2 USB ports (2.0) HDMI/VGA simultaneous video output Support Multi-brand network cameras ONVIF Version 2.4 conformance Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro Processor	1	
2	Indoor Camera 1/2.9" 4MP PS CMOS Image Sensor (0.8758 Centimeters) Max. 4MP (2688 × 1520)/(2560x1440)@25/30 fps Instastream, H.265, H.264, H.264H, H.264B, MJPEG Support Triple stream, WDR (120dB), Day/Night (ICR), 3D NR, ROI, AWB, AGC, BLC, HLC, Digital 3.6mm fixed Lens IR Range of 30 Mtr., Warm Light Range of 30 Mtr., PoE, IP67 Support Built-in Mic	3	
3	Image Sensor: 1/2.7" 8MP Progressive Scan CMOS Effective Pixels: 3840 × 2160 Maximum Resolution: 8MP (4K UHD) Frame Rate: 8MP @ 20 fps, 4MP @ 25/30 fps Lens Type: Motorized Varifocal Focal Length: 2.7 mm – 13.5 mm Max Aperture: F1.4 Video Compression: Interstream, H.265, H.264, H.264H / H.264B, MJPEG (sub-stream) Wide Dynamic Range: 120 dB WDR Noise Reduction: 2D NR / 3D NR, Backlight Compensation: BLC / HLC. White Balance: Auto / Manual / Outdoor / Street lamp, Day/Night Mode: Auto (ICR) / Color / B&W, IR Distance: Up to 60 meters Warm Light Distance: 60 meters, IR LEDs: Multi-core dual light (IR +warm light), Smart IR: Supported	10	
4	Storage – 16 TB	As mentioned	
5	POE Switch, 16 port 10/100/1000 Mbps gigabit ethernet ports, 2 SFP port, 150watts available PoE, Flow control for protection against data loss, Maximum distance of 250m, Light protection 6KV,	1	

	Operating Temperature: 0 to 40 deg C (32 to 104 deg F)		
6	CAT6 UTP Cable (305 mtr) supports Gigabit Ethernet (1000 Base-T) standard. Operates at a bandwidth up to 250 Mhz.	5	
7	HDMI 5 meter, Maximum Resolution: Full HD 1080p Supported Formats: 480p, 720p, 1080i, 1080p, 3D Support: Yes, HDMI Version: Typically, HDMI 1.4 Data Transfer Rate: Up to 18 Gbps HDMI with Ethernet: Supported LED / Smart TV, NVR / DVR, Laptop / Desktop, Projector, Set-top box		
8	PVC BOX for camera	13	
9	6U Rack	1	
10	Online UPS 1 KVA, Capacity: 1 KVA / 800 W, UPS Type: Online Double Conversion Phase: Single Phase Input / Single Phase Output DC System Voltage: 24 VDC Input Voltage Range: 110 VAC \pm 5% – 300 VAC \pm 5% Frequency Range: 40 Hz – 70 Hz Power Factor: \geq 0.99 at full load Phase: Single phase with ground Rated Output Voltage: 200 / 208 / 220 / 230 / 240 VAC Voltage Regulation: \pm 1% (battery mode) Output Waveform: Pure Sine Wave Frequency (Battery Mode): 50 Hz \pm 0.25 Hz or 60 Hz \pm 0.3 Hz Current Crest Ratio: 3:1 Battery Type: SMF (Sealed Maintenance Free) Battery Quantity: 2 \times 12V / 9Ah (In-Built Batteries) Battery Voltage: 24V system Charging Current: 1A Over Voltage Cut-off Device (OVCD), Static Bypass for reliability Short Circuit, Protection Surge Protection, Smart LCD Display	1	
11	LED 43 inch Display Screen Size: 1.08 m (43 inch) Display Type: LED Resolution: 4K UHD (3840 \times 2160), Picture Engine: Crystal Processor, 4K HDR: HDR / HDR10+ supported, Sound Output: 20 W RMS Speaker Type: 2 Channel Object Tracking Sound: OTS Lite, Adaptive Sound: Yes, HDMI Ports: 3 USB Ports: 1 \times USB-A Wi-Fi: Yes (built-in), Bluetooth: Yes RF Input: 1 IP, Control: Yes Power Supply: AC 220–240 V, 50/60 Hz Maximum Power Consumption: ~110 W	1	
12	Conduct Pipe 25 Mm for Cat-6 Wire (Bundle/packet)	4	
13	Conduct Pipe Band for Cat-6 Wire (bundle/packet)	2	
14	Installation and commissioning of complete setup with any accessories required for installation	----	
	Total		

Signature(s)

Name & Address of the firm with seal

Annexure-II: Technical Bid Format

Sr. No.	Particulars	To be filled in by the tenderer
1	Name of the Agency	
3	Date of establishment of the agency	
4	Detailed office address of the Agency with Office Telephone Number, Fax Number and Mobile Number and name of the contact person	
5	Whether the firm is registered under Company Act, partnership, or proprietorship. (Copies of all certificates of registration to be enclosed.)	
6	PAN/TAN Number (copy to be enclosed)	
7	Sales Tax/VAT /GST Registration Number (copy to be enclosed)	
8	Whether the firm is blacklisted by any Government Department or any criminal case is registered against the firm or its owner/partners anywhere in India. (If no, a certificate is to attach in this regard.)	
9	Experience in dealing with Govt. Departments/PSU attach copies of supply orders placed on the agency)	
10	Whether bid document of all pages of the terms and conditions duly signed, in token of acceptance of the same, is attached.	
11	Whether agency profile is attached?	
	Place: Date:	Signature of the Bidder With Office Seal